



**DECLARATION OF PERFORMANCE**  
**in accordance with Annex III of Regulation (EU) No. 305/2011**  
**(Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No 574/2014**

for the product **ARDEX 8 + 9 LW**  
**No. 09321**

1. Unique identification code of the product type: **ETAG 022-1: Assessment Category II**

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Liquid applied watertight covering kits for walls and floors in  
interior wet rooms exposed to temperatures between 5°C and 40°C  
installed beneath a wearing surface**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**ARDEX Skandinavia A/S  
Marielundvej 4  
2730 Herlev  
Denmark**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) of the Regulation (EU) No 305/2011:

**not relevant**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 2+**

6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Not applicable**

6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment was issued:


The notified body **Materialprüfanstalt für das Bauwesen Braunschweig** with the identification number **0761** performed the initial inspection of factory and of factory production control as well as the continuous surveillance, assessment and approval of factory production control.

7. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Crack bridging ability:	Assessment Category 2: 0.75 mm	ETAG 022-1
Bond strength:	Assessment Category 2: $\geq 0.5$ MPa	ETAG 022-1
Joint bridging capability:	Assessment Category 2: watertight	ETAG 022-1
Watertightness around penetrations:	Assessment Category 2: watertight	ETAG 022-1
Resistance to temperature:	Assessment Category 2: $\geq 0.5$ MPa Assessment Category 2: 0.75 mm	ETAG 022-1
Resistance to water:	Assessment Category 2: $\geq 0.5$ MPa	ETAG 022-1
Resistance to alkalinity:	Assessment Category 2: $\geq 0.5$ MPa	ETAG 022-1
Release of dangerous substances:	See material safety data sheet	


8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for the manufacturer and in the name of the manufacturer by:


**ARDEX GmbH**  
 Friedrich-Ebert-Str. 45  
 58453 Witten

---

Dr. Jörg W. Sieksmeier  
 R & D Director

  
 Ann-Kristin Quintern  
 R & D Section Head

Witten, 19<sup>th</sup> November 2020

(Place and date of issue)