

# Sustainability data sheet

## ARDEX F 5

### Fiber reinforced finishing compound

ARDEX F 5 is a brilliant white, cementitious, MICROTEC Fibre Reinforced Repair Mortar.

#### Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

**EMICODE® EC 1<sup>PLUS</sup> R,**  
very low emission



According Emission Classification of Building Materials

**M1**



solvent-free

#### EPD (Environmental Product Declaration)

ARDEX F 5 corresponds to FEICA EPD:

**EPD-FEI-20160042-IBG1-EN**

#### According BASTA

ARDEX F 5 is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See [www.bastaonline.se](http://www.bastaonline.se)



#### Technical Assessment

According **GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):**

**GISCODE ZP1** - cementitious product, low-chromate

**ARDEX F 5 meets the requirements according EN 998-1 : GP-CS IV-W2.**

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)



# ARDEX F 5

Fiber reinforced finishing compound

## Sustainable Building

### Accordinging DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

#### Version 2018

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX F 5 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX F 5 has the GISCODE ZP1 and is certified by EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV.

**ARDEX F 5 fulfills the requirements for highest Quality Level 4.**

#### Version 2015

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX F 5 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX F 5 is certified by EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV.

**ARDEX F 5 fulfills the requirements for highest Quality Level 4.**

### Accordinging LEED (Leadership in Energy and Environmental Design)

#### Version 4 (2014)

##### EQ: Low Emitting Materials

ARDEX F 5 meets the requirements according EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV which are accepted by LEED.

**ARDEX F 5 meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.**

##### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX F 5 corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX F 5 meets the requirements and contributes to achieving one LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

#### Version 2009

##### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

Cementitious fillers are not described by LEED.

##### MR Credit 5.1 und 5.2: Regional Materials

###### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
www.ardex.de

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
kundendienst@ardex.de  
www.ardex.de



# ARDEX F 5

Fiber reinforced finishing compound

## Sustainable Building

According BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

### Version 2016

#### BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX F 5 fulfills the required emission limits and is certified by EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV and by M1 which is accepted as documentation.

**ARDEX F 5 meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.**

According Nordic Swan Ecolabelling

**ARDEX F 5 is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings.**

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 10/01/2019

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)

